



# FIESTA

## Step-by-Step Instruction Leaflet

Please follow these simple and easy instructions to set up your Fiesta folding camper.

.....

Disconnect lighting and ancillary 7 pin plugs, lower jockey wheel and unhitch camper from car.

Apply handbrake and wind down all four corner steadies using handle provided.

Roll up P.V.C. transit cover from the rear, fold in both ends of the roll and secure on the front of the trailer with the P.V.C. retaining flap.

Lift out LH bed through 180° and level so that it is in line with the camper body. **(Note: sighting along both beds will facilitate this function)**

Repeat above function for RH bed.

Unfold wall canvas from top of roof so that it hangs down freely on both sides of camper.

Set all four centre cabin frame poles with the spring button in the bottom of the four adjusting holes.

Swing up ridge poles and joint together by locating spring buttons provided.

Swing up kitchen roof pole to vertical position and extend to set spring buttons in the bottom hole.

Clip the two kitchen extension tension poles into position just above curtain wire holes.

Extend to two diagonal corner roof poles until spring button is in the next to the top hole position.

Secure bottom of canvas all round the camper by hooking the shock cord under the bed boards and pressing the 'Velcro' together under the aluminium moulding.

Finally, tension canvas all round including kitchen extension by means of extending poles until canvas is taut.

Raise kitchen unit to working height by lifting LH side then sliding the unit to the right until it locates in the support channel.

Hang up inner tents and roof lining to the roof poles by means of the hooks attached.

Swing up seat back support arms and locate seat back frame into the arms. Secure seat back cushions in position with the 'Velcro' tapes provided.

Hang up curtains.

## **FIESTA FOLDING DOWN INSTRUCTIONS**

Take down curtains.

Unclip inner tents, fold neatly onto mattress and secure to the bed board with straps provided. (NOTE: if canvas is wet cover beds with the P.V.C. covers fitted to the bed board before strapping down).

Unclip LH side of roof lining and clip onto swing down arms of cabin frame.

Lower kitchen unit to travelling height.

Remove seat back frames and place on floor in front of fridge, swing down support arms to rest on the floor.

Collapse the two corner diagonal roof poles by depressing the spring buttons.

Unclip the shock cord and release the canvas all around the camper.

Set all four cabin frame poles with the spring button in the bottom hole position.

Remove the two kitchen extension tension poles, collapse the roof pole and swing down to rest on top of the kitchen unit.

Disconnect ridge poles by depressing spring buttons and allow ridge poles to swing down to the vertical position. Secure to the intermediate poles using the straps provided.

Fold over front and rear canvas wall neatly onto roof (ensure door zip is closed)

Swing over RH bed first through 180° ensuring that no canvas is trapped between bed and bed support bracket.

Ensure that all four swivel feet lie flat.

Fit transit cover and wind up corner steadies.

Release handbrake and hitch onto car, raise jockey wheel and lock in position.

Connect lighting and ancillary 7 pin plugs.

## **GENERAL NOTES**

The canvas will shrink when wet. To avoid stretching the canvas. Lower all poles by one hole on the adjustment holes. When the canvas is dry the poles can be returned to their original position.

The first time you use your camper in wet weather you may experience a small amount of leakage along the stitching. DO NOT WORRY this is not unusual and after weathering the leaks will cease.

If the camper is folded down whilst wet it should be opened at the earliest opportunity to allow the canvas to dry out.